



FLEXIPLUMB

# Plumbing Made Easy With The Flexiplumb Range

New Innovative And High Quality EPDM Rubber Connections  
For Domestic And Commercial Use



Simple Ways  
To Save Money  
Easy To Fit And  
Do It Yourself!

Compliant with EN 681-2 Standards  
Manufactured in EPDM, (Ethylene Propylene Diene Monomer (M Class)) Rubber

5 Shepherd's Drive  
Carnbane Industrial Estate  
Newry, Co. Down  
N. Ireland, BT35 6JQ  
**Tel:** +44 (0) 28 3083 3081  
**Fax:** +44 (0) 28 3025 7556  
*From ROI*  
**Tel:** (048) 3083 3081  
**Fax:** (048) 3025 7556  
**Web:** [www.EPAS-Ltd.com](http://www.EPAS-Ltd.com)

Award Winning Technology

[www.EPAS-Ltd.com](http://www.EPAS-Ltd.com)

## Straight Connector

### Available in a range of sizes

- Highly flexible allowing for misalignment
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P01-34	34mm	1 ¼"
0635P01-40	40mm	1 ½"
0635P01-54	54mm	2"



## 90° Bend

### Available in a range of sizes

- Highly flexible allowing for misalignment
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P02-34	34mm	1 ¼"
0635P02-40	40mm	1 ½"
0635P02-54	54mm	2"



## Tee Piece

### Available in a range of sizes

- Highly flexible allowing for misalignment
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P03-34	34mm	1 ¼"
0635P03-40	40mm	1 ½"
0635P03-54	54mm	2"



## Running Trap

### Available in a range of sizes

- Add to plumbing run at the source of the problem
- Simply squeeze the running trap to clear blockages and save money!
- Stop bad odours
- Highly flexible allowing for misalignment
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P04-34	34mm	1 ¼"
0635P04-40	40mm	1 ½"
0635P04-54	54mm	2"



## Adaptor

### Available in a range of sizes

- Compatible with all Imperial and Metric Sizes
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P05-34/40	34/40mm	1 ¼"
0635P05-34/54	40/54mm	1 ½"
0635P05-40/54	40/54mm	2"



## P Trap

### Available in a range of sizes

- Installed underneath the sink
- Simply squeeze to clear blockages and save money!
- Stops bad odours
- Highly flexible allowing for misalignment
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P06-34	34mm	1 ¼"
0635P06-40	40mm	1 ½"
0635P06-54	54mm	2"



## Sampling Point

### Tee Reducer and Drain Valve

- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
1905P05	54mm	2"



## Boss 50mm

### Pipe Fitting Reducer

- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P07	110/50mm	4" / 2"



## Boss 34/40mm

### Pipe Fitting Reducer

- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P08	110/32/42mm	4" / 1 1/4" / 1 1/2"



## Endcap

### Available in a range of sizes

- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P10-34	34mm	1 1/4"
0635P10-40	40mm	1 1/2"
0635P10-54	54mm	2"



## Flexible Hose

### Available in a range of sizes

- Increases flexibility for installation
- Increases mobility for GreaseShield, Integrated Work Station etc.
- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0604P19-1.5	40mm	1 1/2"
060419-2.0	54mm	2"



## 45° Bend

### Available in a range of sizes

- Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0635P12-34	34mm	1 1/4"
0635P12-40	40mm	1 1/2"
0635P12-54	54mm	2"



## Sewer Fixing Bracket

### Fixed pipes or fittings

- Material - Copolymer-Polypropylene/ Polyethylene • Operating Temperature 15°C- 130°C

PART NO.	NOMINAL PIPE OD	IMPERIAL SIZE
0604P38-A-54	54mm	2"



# FLEXIPLUMB

## Flexiplumb Range

### Key Benefits

- ✓ Ease of installation with stainless steel jubilee clip
- ✓ Easy to fit and do it yourself
- ✓ Highly flexible allowing for misalignment
- ✓ Freedom from corrosion

### Key Applications

- ✓ Commercial Kitchens
- ✓ Hotels
- ✓ Domestic Applications etc.



**Environmental Products and Services also offer a wide range of Copper and Plastic plumbing fittings.**

Contact: [Info@EPAS-Ltd.com](mailto:Info@EPAS-Ltd.com) for more details.