

Technical Specification - GreaseShield® 1000-DPE



DRAWER PRE-FILTER FOR SOLID WASTE SEPARATION



GreaseShield®

The Grease Management Solution

APPLICATIONS

- Single Bowl Pot Wash Sinks
- Pre-Rinse Sinks
- Hood Dishwashers

FLOW RATE & SPECIFICATION

- Pro-Active Flow Rate - 1.0 L/s
- Solid Waste Retention Capacity - 6.5 Litres

STANDARD FEATURES & FUNCTIONS

- Automatic FOG & solids removal
- Drawer Pre-Filter for solids waste separation and retention
- Filtration Basket with a 0.7mm fine mesh base, for smaller particle retention
- Self cleaning
- Magnetic baffle for bioremediation
- PLC controlled
- Non restricted Vortex Flow Control device
- Reverse flow configuration
- Grey water recirculation
- Globally certified award winning technology

Plumbing Connections

Drawer Pre-Filter Inlet	1.5"/40mm
Outlet	2"/54mm
Decant Outlet	¾"/18mm
Hot Water Solenoid	¾"/22mm

Electrical Ratings

	USA	UK,EU,AU,NZ
Voltage	120v	230v
Frequency	60Hz	50Hz
Current	0.98A	0.49A

Standard Operational Times

Days of Operation	7 Days a Week
Hours of Operation	07:00-02:30

Note: Operational times should be adjusted to suit the needs of the kitchen

Average Power Consumption

TBD

EPAS CERTIFICATIONS & APPROVALS

- PDI G101 (Plumbing & Drainage Institute)
- ASME A112.14.3 & A112.14.4 (American Society of Mechanical Engineers)
- NSF International (National Sanitation Foundation)
- CSA (Canadian Standards Association) - Grease Interceptors
- UL (Underwriters Laboratory)
- IAPMO (International Association of Plumbing and Mechanical Officials) Uniform Plumbing Code Certification Mark
- UKCA (UK Conformity Assessed)
- CE - Conformity with Health, Safety and Environmental Protection \ Standards with the European Economic Area (EEA)
- EN1825 (European Standard for Grease Separators)
- KIWA (ETA DK, Swedac & SINTEF) - Sweden, Norway and Finland.
- European Institution for Testing, Inspection and Certification
- SHASE-S 217:2016 (Japanese Grease Management Standard for Grease Interceptors)



**Environmental
Products and Services Ltd**

Award Winning Technology

www.GreaseShield.com

HEAD OFFICE +44 (0) 28 3083 3081


sales@epas-ltd.com

GB OFFICE +44 (0) 161 477 5555



V3 11/09/2024

Technical Specification - GreaseShield®1000-DPF

GreaseShield® The Grease Management Solution



SPACE REQUIRED TO PULL OUT DRAWER AND REMOVE FILTER BASKETS



DECANT OUTLET Ø 3/4" 18mm
INLET Ø 1.5" 40mm
OUTLET Ø 2" 54mm



Environmental
Products and Services Ltd

Award Winning Technology

www.GreaseShield.com

HEAD OFFICE +44 (0) 28 3083 3081

sales@epas-ltd.com

GB OFFICE +44 (0) 161 477 5555

V3 11/09/2024