



# Technical Specification - GreaseShield® 3000-DW



**PRE-FILTER  
FOR SOLID WASTE  
SEPARATION**

## GreaseShield®

The Grease Management Solution

### APPLICATIONS

- Conveyor/Tunnel Dishwashers
- Pot-Wash & Pre-Rinse Sinks

### FLOW RATES & CERTIFICATION

- Pro-Active Flow Rate - 3 L/sec
- ASME Certification
- CSA Certification
- EN 1825 Certification

### STANDARD FEATURES & FUNCTIONS

- Automatic FOG & solids removal
- Self cleaning
- Magnetic baffle for bioremediation
- PLC controlled
- Reverse flow configuration
- Grey water recirculation
- Globally certified award winning technology
- The only Green Certified grease trap in the world



**Environmental  
Products and Services Ltd**

Award Winning Technology

### Plumbing Connections

Inlet	2"/54mm
Outlet	3"/76mm
Hot Water Solenoid	3/4"/22mm

### Electrical Ratings

	USA	UK,EU,AU,NZ
Voltage	120v	230v
Frequency	60Hz	50Hz
Current	0.98A	0.49A

### Standard Operational Times

Days of Operation	7 Days a Week
Hours of Operation	07:00-02:30

Note: Operational times should be adjusted to suit the needs of the kitchen

### Average Power Consumption

15.8W Per Hour

### CERTIFICATIONS & APPROVALS

- Global GreenTag LCA Rate Gold Certification
- ASME A112.14.3 & A112.14.4 (American Society of Mechanical Engineers)
- NSF International (National Sanitation Foundation)
- CSA (Canadian Standards Association) - Grease Interceptors
- UL (Underwriters Laboratory)
- IAPMO (International Association of Plumbing and Mechanical Officials) Uniform Plumbing Code Certification Mark
- UKCA (UK Conformity Assessed)
- CE - Conformity with Health, Safety and Environmental Protection \ Standards with the European Economic Area (EEA)
- EN1825 (European Standard for Grease Separators)
- KIWA (ETA DK, Swedac & SINTEF) - Sweden, Norway and Finland.
- European Institution for Testing, Inspection and Certification
- SHASE-S 217:2016 (Japanese Grease Management Standard for Grease Interceptors)

V12 11/12/2024



[www.GreaseShield.com](http://www.GreaseShield.com)

HEAD OFFICE +44 (0) 28 3083 3081

[sales@epas-ltd.com](mailto:sales@epas-ltd.com)

GB OFFICE +44 (0) 161 477 5555

# Technical Specification - GreaseShield® 3000-DW



**HEIGHT REQUIRED FOR FILTER BASKET REMOVAL**



**SPACE REQUIRED FOR LID REMOVAL AND ACCESS**

**SPACE REQUIRED FOR END PLATE REMOVAL AND ACCESS**



**Environmental Products and Services Ltd**

Award Winning Technology

[www.GreaseShield.com](http://www.GreaseShield.com)

HEAD OFFICE +44 (0) 28 3083 3081

[sales@epas-ltd.com](mailto:sales@epas-ltd.com)

GB OFFICE +44 (0) 161 477 5555

V12 11/12/2024