# Technical Specification - GreaseShield®1000-Defender





## **APPLICATIONS**

- Prep Sinks
- Small Pot Wash Sinks

#### FLOW RATES & CERTIFICATION

- Pro-Active Flow Rate 1 L/sec
- ASME Certification
- PDI Certification
- CSA Certification
- EN 1825 Certification

## STANDARD FEATURES & FUNCTIONS

- Automatic FOG & solids removal
- Self cleaning
- Magnetic baffle for bioremediation
- PLC controlled
- Reverse flow configuration
- Space Saver Running Trap & Sampling Point
- Globally certified award winning technology
- The only Green Certified grease trap in the world



#### **Plumbing Connections**

FilterShield™ Inlet 1"½/40mm Inlet 1"¼/32mm Outlet 2"/50mm Hot Water Solenoid ¾/"/22m

Electrical RatingsUSAUK,EU,AU,NZVoltage120v230vFrequency60Hz50HzCurrent0.98A0.49A

#### Standard Operational Times

Days of Operation 7 Days a Week Hours of Operation 07:00-02:30

Note: Operational times should be adjusted to suit the needs of the kitchen

**Average Power Consumption** 15.1W Per Hour

## **CERTIFICATIONS & APPROVALS**

- Global GreenTag LCA Rate Gold Certification
- PDI G101 (Plumbing & Drainage Institute)
- ASME A112.14.3 & A112.14.4 (American Society of Mechanical Engineers)
- NSF International (National Sanitation Foundation)
- CSA (Canadian Standards Association) Grease Interceptors
- UL (Underwriters Laboratory)
- IAPMO (International Association of Plumbing and Mechanical Officials) Uniform Plumbing Code Certification Mark
- UKCA (UK Conformity Assessed)
- CE Conformity with Health, Safety and Environmental Protection \Standards with the European Economic Area (EEA)
- EN1825 (European Standard for Grease Separators)
- KIWA (ETA DK, Swedac & SINTEF) Sweden, Norway and Finland.
  European Institution for Testing, Inspection and Certification
- SHASE-S 217:2016 (Japanese Grease Management Standard for Grease Interceptors)

V4 07/07/2022



# Technical Specification - GreaseShield®1000-Defender

