FlexiPlumb Flexible Plumbing Fittings



KEY FEATURES

- Flexible connection to compensate for plumbing misalignment.
- Quick and easy to install and remove.
- Adjustable and can be used on mismatched pipe sizes.
- Allows for easy access for pipework servicing and repairs.
- Creates an excellent seal around existing pipework.
- Highly durable and suitable for long term application.
- Compatible with conventional solvent weld, push fit and compression waste systems.
- No adhesives required.

SPECIFICATION

Material - EPDM Rubber (Ethylene Propylene Diene Monomer)

Made to British & European Standard - BS-EN-681-1

High resistance to water, heat, chemicals aging and ozone/weathering.

Operating Temperature - 15°C-130°C

Fastened with Stainless-Steel worm drive hose clamps.








FLEXIPLUMB - STRAIGHT CONNECTOR






Fitting Size	34mm (1½")	40mm (1½")	54mm (2")
(A) Internal Diameter	34mm (1.3")	40mm (1.6")	54mm (2.1″)
(B) External Diameter	45mm (1.8")	51mm (2")	65mm (2.6")
(C) Insertion Depth	30mm (1.2″)	33mm (1.3″)	36mm (1.4")
(D)	64mm (2.5″)	70mm (2.8″)	76mm (3″)

FLEXIPLUMB - 90° BEND






Fitting Size	34mm (1¼″)	40mm (1½″)	54mm (2")
(A) Internal Diameter	34mm (1.3″)	40mm (1.6″)	54mm (2.1")
(B) External Diameter	45mm (1.8″)	51mm (2")	65mm (2.6")
(C) Insertion Depth	30mm (1.2″)	33mm (1.3″)	36mm (1.4")
(D)	57mm (2.2")	64mm (2.5″)	75mm (3")
(E)	80mm (3.1″)	90mm (3.5″)	108mm (4.3″)

FLEXIPLUMB - 45° BEND






Fitting	34mm	40mm	54mm
Size	(1¼″)	(1½″)	(2")
(A) Internal Diameter	34mm (1.3")	40mm (1.6″)	54mm (2.1″)
(B) External Diameter	45mm (1.8″)	51mm (2″)	65mm (2.6″)
(C) Insertion Depth	30mm (1.2″)	33mm (1.3″)	36mm (1.4")
(D)	68mm	77mm	93mm
	(2.7")	(3″)	(3.7")
(E)	89mm	99mm	114mm
	(3.5")	(3.9")	(4.5")

FLEXIPLUMB - ADAPTOR REDUCER






Fitting	34-40mm	34-54mm	40-54mm
Size	(1¼-1½")	(1¼-2")	(1½-2")
(A) Internal	34mm	34mm	40mm
Diameter 1	(1.3")	(1.3")	(1.6")
(B) Internal	40mm	54mm	54mm
Diameter 2	(1.6")	(2.1")	(2.1")
(C) External	44mm	44mm	50mm
Diameter 1	(1.7")	(1.7")	(2")
(D) External	50mm	64mm	64mm
Diameter 2	(2")	(2.5")	(2.5")
(E) Insertion	30mm	30mm	33mm
Depth 1	(1.2")	(1.2")	(1.3")
(F) Insertion	33mm	36mm	36mm
Depth 2	(1.3")	(1.4")	(1.4")
(G)	75mm	78mm	81mm
	(3″)	(3.1")	(3.2")



FLEXIPLUMB - TEE CONNECTOR






Fitting	34mm	40mm	54mm
Size	(1¼")	(1½″)	(2")
(A) Internal	34mm	40mm	54mm
Diameter	(1.3")	(1.6")	(2.1")
(B)External	45mm	51mm	65mm
Diameter	(1.8")	(2")	(2.6")
(C) Insertion	30mm	33mm	36mm
Depth	(1.2")	(1.3")	(1.4")
(D)	57mm	66mm	73mm
	(2.2")	(2.6")	(2.9")
(E)	80mm	92mm	106mm
	(3.1″)	(3.6")	(4.2")
(F)	114mm	132mm	146mm
	(4.5″)	(5.2")	(5.7")

FLEXIPLUMB - ENDCAP






Fitting Size	34mm (1¼″)	40mm (1½″)	54mm (2")
(A) Internal Diameter	34mm (1.3″)	40mm (1.6″)	54mm (2.1")
(B) External Diameter	46mm (1.8")	50mm (2")	64mm (2.5")
(C) Insertion Depth	30mm (1.2")	34mm (1.3″)	40mm (1.6″)
(D)	34mm (1.3″)	38mm (1.5″)	44mm (1.7″)

FLEXIPLUMB - RUNNING TRAP






Fitting	34mm	40mm	54mm
Size	(1¼″)	(1½″)	(2")
(A) Internal Diameter	34mm (1.3")	40mm (1.6″)	54mm (2.1″)
(B) External Diameter	45mm (1.8")	51mm (2")	65mm (2.6")
(C) Insertion Depth	30mm (1.2")	33mm (1.3″)	36mm (1.4")
(D)	110mm	124mm	154mm
	(4.3″)	(4.9″)	(6.1″)
(E)	180mm	202mm	244mm
	(7.1″)	(8")	(9.6")

FLEXIPLUMB - P TRAP






Fitting	34mm	40mm	54mm
Size	(1¼")	(1½″)	(2")
(A) Internal Diameter	34mm (1.3")	40mm (1.6″)	54mm (2.1″)
(B) External Diameter	45mm (1.8")	51mm (2")	65mm (2.6″)
(C) Insertion Depth	30mm (1.2")	33mm (1.3″)	36mm (1.4")
(D)	133mm	143mm	169mm
	(5.2")	(5.6")	(6.7")
(E)	128mm	140mm	174mm
	(5")	(5.5″)	(6.9")



FLEXIPLUMB - SEWER BOSS






Fitting Size	110-34/40mm (4-1¼/1½″)	110-50mm (4-2")
(A) Internal Diameter 1	34mm (1.3")	50mm (2")
(B)External Diameter	40mm (1.6")	N/A
(C) Insertion Depth	98mm (3.6")	98mm (3.6")
(D)	42mm (1.7")	42mm (1.7")
(E)	54mm (2.1")	54mm (2.1")
(F)	122mm (4.8")	122mm (4.8″)

FLEXIPLUMB - SPACE SAVER RUNNING TRAP








Fitting Size	54mm (2")
(A) Internal Diameter	54mm (2.1")
(B) External Diameter	65mm (2.6")
(C) Insertion Depth	32mm (1.3")
(D)	138mm (5.4")
(E)	141mm (5.6″)
(F)	112mm (4.4")
(G)	76mm (3")
(H)	13mm (0.5")

FLEXIPLUMB - SAMPLING POINT






Fitting Size	54mm (2")
(A) Internal Diameter	54mm (2.1")
(B) External Diameter	65mm (2.6")
(C) Insertion Depth	35mm (1.4")
(D)	96mm (3.8")
(E)	107mm (4.2")

FLEXIPLUMB - VORTEX FLOW CONTROLLER





Fitting Size	40mm (1½″)
(A) Internal Diameter	40mm (1.6")
(B) External Diameter	48mm (1.9")
(C) Insertion Depth	82mm (3.2")
(D)	48mm (1.9")
(E)	88mm (3.5")
(F)	154mm (6.1")
(G)	144mm (5.7")